

----- 1. PRODUCT IDENTIFICATION -----

TRADE NAME (as labeled): LATICRETE MultiMastic #15 Tile Adhesive

USE: Tile Adhesive

MANUFACTURER'S NAME: LATICRETE Australia Pty Ltd
29 Telford Street
Virginia. QLD. 4014

For additional information: 07 38651599, 1800 331 012

Web address: www.laticrete.com.au

Poisons Information Number: 131126

Date prepared or revised: 06/07/22

----- 2. HAZARDS IDENTIFICATION -----

Classification: Not Hazardous according to the criteria of the NOHSC. Not classified as a Dangerous Goods substance according to the ADG code. Not classified as a scheduled poison according to the SUSDP. Not classified as a flammable or combustible liquid according to the criteria of AS 1940.

Risk Phrases: R36/37/38 Irritating to eyes, respiratory system and skin. R66 Repeated exposure may cause skin dryness and cracking.

Safety Phrases: S24 Avoid contact with the skin. S25 Avoid contact with eyes. S25 In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. S28 After contact with skin was immediately with plenty of soap. S36/37/38 Wear suitable protective clothing, gloves and eye/face protection.

----- 3. COMPOSITION / INFORMATION ON INGREDIENTS-----

CHEMICAL NAMES	CAS NUMBERS	PERCENT
Calcium Carbonate	1317-65-3	30-65
Other ingredients determined at level not to be hazardous		To 100%

----- 4. FIRST AID MEASURES-----

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhalation: Vapour may cause slight irritation to upper respiratory tract. No adverse effects are anticipated from inhalation incidental to normal exposure.

Contact with eyes: Eye contact may cause slight, temporary eye irritation. If symptoms persist seek medical attention.

Contact with Skin: Short exposure not likely to cause significant skin irritation. Skin absorption is unlikely due to physical properties.

Swallowed: ~~Single dose oral toxicity is believed to be low.~~ No hazards anticipated from ingestion incidental to industrial exposure.

FIRST AID or EMERGENCY PROCEDURES

Disposal: Recycle wherever possible or consult manufacturer for recycling options. Dispose of in an authorized landfill according to federal, state and local regulations.

----- **7. HANDLING AND STORAGE** -----

Handle with suitable protective clothing. Avoid skin or eye contact.

Check all containers are clearly labeled and free from leaks.

Storage Requirement

Store in a cool, dry ventilated place between 1 -35 °C. Protect containers against physical damage and check regularly for leaks. Observe manufacturers storing and handling recommendations.

----- **8. EXPOSURE CONTROLS & PERSONAL PROTECTION**-----

No exposure standards for this product have been set OR not found in our records.

Ventilation and engineering controls: If used externally, natural ventilation is generally adequate. If used in enclosed spaced with poor ventilation provide mechanical ventilation to comfort levels.

Respiratory protection (type): No respiratory protection is should be required if good ventilation is maintained. Use respirators fitted with organic vapour filters to AS1715 & AS1716 in areas with high vapour concentrations.

Eye protection (type): Use a chemical goggle or safety glasses with side shields or safety glass to AS1337.

Gloves (specify material): Use impervious gloves, vinyl or rubber to AS2161

Other clothing and equipment: Wear clean, long-sleeved, body covering clothing.

Work practices, hygienic practices: Familiarize the employees with the handling procedures in this section; also encourage prompt removal of contaminated clothing and clearing of contaminated areas.

----- **9. PHYSICAL AND CHEMICAL PROPERTIES**-----

Vapor density (air=1): N/A

Melting point or range, °C: N/A

Specific gravity: 1.6

Boiling point or range, °C: 100

Solubility in water: Miscible

Evaporation rate (butyl acetate = 1): N/A

Vapor pressure, mmHg at 20 °C: 0mm

pH: 10

Appearance and odour: White paste, slight acrylic odour

----- **10. REACTIVITY DATA** -----

Stability: X Stable Unstable

Conditions to avoid: Excessive heat and freezing

Incompatibility (materials to avoid): Strong oxidizers and caustics.

Hazardous decomposition products (including combustion products): (from burning, heating or reaction with other material): None

Hazardous polymerization: _____ May occur _____ X _____ Will not occur

----- 11 . TOXICOLOGICAL INFORMATION -----

No relevant product data found

----- 12. ECOLOGICAL CONSIDERATIONS-----

May have an adverse effect on aquatic organisms if large amounts are released to waterways.

----- 13. DISPOSAL CONSIDERATIONS-----

Dispose of all wastes in accordance with federal, state and local regulations for non-hazardous chemical wastes

----- 14. TRANSPORT CONSIDERATIONS-----

Requirements under the ADG code, IMDG code, or the IATA DG code do not apply to this product

----- 15. REGULATORY INFORMATION-----

Label in accordance with the National Code of Practice for the Labeling of Workplace Substance (NOHSC: 2012 (1994)): Labeling under the SUSDP or the ADG Code is not required.

----- 16. OTHER INFORMATION-----

This information is furnished without warranty, representation, inducement, or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate. Persons dealing with the products referred to in this MSDS do so at their own risk since their actions are beyond our control. Laticrete Pty Ltd accepts no liability whatsoever for damage or injury arising from the use of the information contained in this document. This document should be made available to all operators who may come into contact with this product.